

R3-1400 ROBOWASH MACHINE

R3-1400

FEATURES & SPECS



MACHINE DESCRIPTION

The R3-1400 Robowash machine delivers superior aqueous parts cleaning performance with the labour saving convenience of automation.

Suited to general all round cleaning applications in the trucking and transport industry with a basket size of 1400mm, an internal height of 600mm and a standard weight range of 750kg.

The R3-1400 Robowash machine comes standard with full insulation, open lid design, side tables for loading and unloading, automatic water top up circuitry, heater element protection circuitry and electronic thermostat water temperature control.

MACHINE SPECIFICATIONS

Load Capacity: 750 kg

Basket Dimensions: 1400mm

Internal Height: 600 mm

Tank Capacity: 280 L

Max Electrical Load: 20A 3 phase

Machine Weight: 600 kg

KEY FEATURES

- Heavy gauge 3mm mild steel and optional 3mm 316 stainless steel construction
- Fully adjustable cleaning settings including wash cycle times, basket speed and temperature
- Tamper proof lid latch with safety shut down circuit
- Robogun hand-held high-pressure cleaning attachment
- Patented automatic braking system with optional emergency stop, 7 day digital timer and lid safety stop.





MACHINE SPECIFICATIONS

Width - right side table*

Width - both side tables

Comments







R3-1400 ROBOWASH MACHINE

R3-1400

FEATURES & SPECS

INSTALLATION REQUIREMENTS

Installation Requirements for Model R3-1400

CONNECTIONS REQUIRED

All connections are required to be dedicated and permanent.

ELECTRICAL

Wall plug at the rear of but no further than 5 metres from the machine.

• Option A: 415V, 20 A, 3 phase with Earth (4 pin plug) without purge pump.

• Option B: 415 V, 20 A, 3 phase with Earth and Neutral

(5 pin plug) with purge pump.

AIR

Supply to the rear but no further than 5 metres from the machine. 320 series double button hose connection. 3 bar minimum.

WATER

Supply to the rear of but no further than 5 metres from the machine. 0.5" garden hose cock on a main pressure line. Must be permanent for Automatic Top Up Circuitry.

MACHINE SERVICING & WASTE REMOVAL

WASTE WATER

Robowash Service: Access for Vacuum Tank to remove waste water from machine. No further than 20 metres.

Self Service: Waste water storage tank / IBC at the rear of but no further than 10 metres from the machine. Requires additional purge pump assembly.

Model	R3-1400
Load Capacity	750 kg
Basket Dimensions	1400 mm Diameter
Internal Height	600 mm
Tank Capacity	280 L
Pump Motor	415 v 3 Phase 4kW 9.0A Max
Pump Water pressure	380 - 485kPa (55 - 70psi)
Pump Mechanical Seal type	Carbon / Ceramic / NBR
Pump Mechanical Seal type Elements	Carbon / Ceramic / NBR 12.0A
, ,,	
Elements	12.0A
Elements Max Electrical Load	12.0A 20.0A - 3 Phase
Elements Max Electrical Load Machine Weight	12.0A 20.0A - 3 Phase 600 kg
Elements Max Electrical Load Machine Weight Overall height (lid closed)	12.0A 20.0A - 3 Phase 600 kg 1310 mm

1950 mm

2900 mm

*Right side table fixed

with brake added

