

SOLVENT SINKS

SOLVENT SINKS FEATURES & SPECS



DESCRIPTION

When manual cleaning of smaller components is required Robowash offers solvent sinks for your specific cleaning requirements. The solvent sinks are designed for safety and convenience and we offer both traditional hydrocarbon solvents as well as environmentally friendly water-based solvents.

The Robowash solvent sinks is suited to smaller parts cleaning applications with sink dimensions of 800mm width, 550mm depth and 250mm height.

SPECIFICATIONS

Solvent Sink dimensions:	Internal Sink Width:	800mm
	Internal Sink Depth:	550mm
	Internal Sink Height:	250mm
Tank capacity:	60 litres	
Electrical load:	10A, 240V Single Phase	
Pump:	10 LPM	

KEY FEATURES

- Simple to use and cost effective
- Solvent options for all types of applications
- Electrical and pneumatic pumps are available
- Filters available to reduce contamination
- Rinse or wash function in the same machine

SOLVENT SINKS

SOLVENT SINKS FEATURES & SPECS

INSTALLATION REQUIREMENTS

Installation Requirements for RS800

CONNECTIONS REQUIRED

All connections are required to be dedicated and permanent.

ELECTRICAL

Wall plug at the rear of but no further than 5 metres from the machine.

- 240V 10A single phase

AIR

Only required for optional pneumatic pump.
Supply to the rear but no further than 5 metres from the machine.
320 series double button hose connection.
3 bar minimum.

SPECIFICATIONS

Model	RS800
Load Capacity	250 kg
Solvent Sink Dimensions	Internal Sink Width: 800mm Internal Sink Depth: 550mm Internal Sink Height: 250mm
Tank Capacity	60 L
Pump Motor	Single Phase 10.3A
Pump pressure	10 LPM
Total Electrical Load	Single Phase 10.3A
Overall height (lid closed)	1100mm
Clearance height (lid open)	1700mm
Depth	700mm
Width	950mm

